

JETMASTERS

LIMITED



Bank Chambers, 29 High Street, Ewell, Surrey, KT17 1SB
Tel: ++ 44 (0) 208 337 0033 Fax: ++ 44 (0) 208 337 0034 email: info@jetmasters.co.uk
www.jetmasters.co.uk



WX VAN PACK

PUMP	Triplex ceramic plunger, positive displacement, self-priming with oil bath splash lubrication, alloy-bronze head. Automatic unloader valve. Anti-freeze facility providing full protection against frost damage.
TRANSMISSION	Close coupled gearbox.
ENGINE	Kohler industrial 25HP petrol engine, V-twin air cooled with electric start, automatic low oil pressure cut out.
MOUNTING	Pump and engine skid mounted and fitted with 50 gallon (250 litres) fabricated plastic water break tank, filter, drain valve, double inlet check valves and stainless steel diverter valve. Frame fabricated in box section steel, shot blasted & powder coated.
HOSE REELS	High-pressure delivery manual hose reel with handle. Inlet hose reel.
ACCESSORIES	Included with unit 60 metres high-pressure delivery hose and 25 metres of 3/4" inlet hose. Dry shut gun/lance with fan and straight jets, two 1/2" standard drain jets, and 20' mini jet kit.
OPTIONS	28mm spinning jet for clearing fat £320.00 Digital tachometer/engine hour counter £ 70.00 Remote Control £820.00
DIMENSIONS	Height 1090mm Width 830mm Length 1200mm Weight 290kg
PERFORMANCE	8 gpm @ 3000 psi
PRICE EX WORKS	£5,286
FITTING	Included
AVAILABILTY	3 to 4 weeks
TERMS	30% with order, 70% on collection by Bankers Draft
VAT	Will be added to the above prices at the current rate

RTD/0310

JETMASTERS

LIMITED



Bank Chambers, 29 High Street, Ewell, Surrey, KT17 1SB
Tel: ++ 44 (0) 208 337 0033 Fax: ++ 44 (0) 208 337 0034 email: info@jetmasters.co.uk
www.jetmasters.co.uk



P50 Van Pack

PUMP	Speck P45 Triplex ceramic plunger, positive displacement, self-priming with oil bath splash lubrication, alloy-bronze head. Anti-freeze facility providing full unit protection against frost damage.
TRANSMISSION	Pulley/timing belt reduction.
ENGINE	Industrial 4 cylinder water 54hp cooled diesel engine with 12 volt electric start, variable speed. Engine fitted with automatic shut-down on low oil pressure and high water temperature.
MOUNTING	Pump and engine assembly mounted on a sub-frame with flexible mounts to skid mount and fitted with 100 gallon fabricated plastic water break tank with integral 25 litre anti-freeze solution tank, double filtration, drain valve, and inlet ball valve. Skid mount fabricated in box-section. Grouped controls: throttle control, key switch start and stop, pressure gauge, hour counter and stainless steel diverter valve.
HOSE REELS	300' capacity high pressure delivery hose reel with hydraulic wind/rewind. Low pressure inlet hose reel.
ACCESSORIES	Included with unit 300' high-pressure delivery hose and 25 metres of 3/4" inlet hose, dry-shut wash down gun with fan and straight jets, two 1/2" standard drain jets, plough jet, and 20' mini jet kit.
PERFORMANCE	13 gpm @ 4000 psi Optionally 17 gpm @ 3000 psi (Additional £490.00)
DIMENSIONS	Weight: Dry 700kg. With Water 1150kg L: 1.53m W: 1.12m H: 1.20m
AVAILABILITY	4 to 6 Weeks
PRICE EX WORKS	£13,255.00
FITTING	Included
TERMS	30% with order, 70% on collection by Bankers Draft

Prices ex-works and subject to VAT. Specification subject to change without notice.

RTD/0310